


FILTEC®+
METRIC

Ø x pitch	x d	D : base tapping length	CODE 127 : Filtec+ 125 : Filtec+vert 104 : Lockfil+	H : nb. of turns at the initial state Tolerance -0,25	G : Ø initial state min - max	A : Drilling		Tapping	
						Ø drill	Tolerance min max	B : Ø ext. min	C : Ø outer
M 11 x 1,50	1 d	11,00	127 11 03 11 00	5,60	13,05 13,35	11,50	11,324 + 0,236	12,948	11,974 + 0,115
	1,5 d	16,50	127 11 03 16 50	9,00					
	2 d	22,00	127 11 03 22 00	12,35					
	2,5 d	27,50	127 11 03 27 50	15,75					
	3 d	33,00	127 11 03 33 00	18,95					
M 12 x 1,00	1 d	12,00	127 12 01 12 00	9,75	13,70 14,10	12,30	12,217 + 0,190	13,300	12,650 + 0,100
	1,5 d	18,00	127 12 01 18 00	15,20					
	2 d	24,00	127 12 01 24 00	20,50					
	2,5 d	30,00	127 12 01 30 00	25,95					
	3 d	36,00	127 12 01 36 00	31,30					
M 12 x 1,25	1 d	12,00	127 12 02 12 00	7,75	13,75 14,05	12,40	12,271 + 0,212	13,624	12,812 + 0,114
	1,5 d	18,00	127 12 02 18 00	12,15					
	2 d	24,00	127 12 02 24 00	16,65					
	2,5 d	30,00	127 12 02 30 00	21,15					
	3 d	36,00	127 12 02 36 00	25,65					
M 12 x 1,50	1 d	12,00	127 12 03 12 00	6,30	14,10 14,40	12,50	12,324 + 0,236	13,948	12,974 + 0,125
	1,5 d	18,00	127 12 03 18 00	10,00					
	2 d	24,00	127 12 03 24 00	13,80					
	2,5 d	30,00	127 12 03 30 00	16,00					
	3 d	36,00	127 12 03 36 00	21,25					
M 12 x 1,75	0,75 d	9,00	127 12 04 09 00	3,70	14,35 14,60	12,50	12,379 + 0,265	14,274	13,137 + 0,134
	1 d	12,00	127 12 04 12 00	5,20					
	1,25 d	15,00	127 12 04 15 00	6,90					
	1,5 d	18,00	127 12 04 18 00	8,40					
	2 d	24,00	127 12 04 24 00	11,75					
	2,5 d	30,00	127 12 04 30 00	14,75					
	3 d	36,00	127 12 04 36 00	18,05					
M 14 x 1,50	0,75 d	10,50	127 14 03 10 50	5,40	16,25 16,65	14,50	14,324 + 0,236	15,948	14,974 + 0,125
	1 d	14,00	127 14 03 14 00	7,50					
	1,5 d	21,00	127 14 03 21 00	11,85					
	2 d	28,00	127 14 03 28 00	16,15					
	2,5 d	35,00	127 14 03 35 00	20,10					
	3 d	42,00	127 14 03 42 00	24,55					
M 14 x 2,00	0,75 d	10,50	127 14 05 10 50	4,00	16,80 17,15	14,50	14,433 + 0,300	16,598	15,299 + 0,145
	1 d	14,00	127 14 05 14 00	5,60					
	1,25 d	17,50	127 14 05 17 50	7,20					
	1,5 d	21,00	127 14 05 21 00	8,80					
	2 d	28,00	127 14 05 28 00	12,00					
	2,5 d	35,00	127 14 05 35 00	15,20					
	3 d	42,00	127 14 05 42 00	18,40					